


F03 Ø35mm SOFT-CLOSING INDIVISIBLE SHORT ARM HINGE
35杯缓冲固装短臂铰链




- 开启角度: 100度
- 铰杯厚度: 10.5毫米
- 铰杯直径: 35毫米
- 面板(K)尺寸: 3毫米-7毫米
- 材质: 铁镀镍
- 门可选用板厚: 14毫米-20毫米
- Opening angle: 100°
- Depth of hinge cup: 10.5mm
- Diameter of hinge cup: 35mm
- Drilling distance on the door(K): 3-7mm
- Material: cold rolled steel, nickel plated
- Range of door thickness: 14-20mm


F03系列内置阻尼自动铰链功能图 F03 Installation dimensions D: 盖位计算值表 Overlay
A: 间隙位计算值表 Gap



$\begin{matrix} H & K \\ D \end{matrix}$	3	4	5	6	7
0	17	18	19	20	21
2	15	16	17	18	19
4	13	14	15	16	17



$\begin{matrix} H & K \\ D \end{matrix}$	3	4	5	6	7
0	8	9	10	11	12
2	6	7	8	9	10
4	4	5	6	7	8



$\begin{matrix} H & K \\ A \end{matrix}$	3	4	5	6	7
0	1	0	-1	-2	-3
2	3	2	1	0	-1
4	5	4	3	2	1

